## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Gnosjö Konstsmide AB

Supplier's address: -

## Model identifier: 3957-207

## Type of light source:

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS |  |  |  |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type         | -    |                                 |      |  |  |  |
| (or other electric interface) |      |                                 |      |  |  |  |
| Mains or non-mains:           | MLS  | Connected light source (CLS):   | Nein |  |  |  |
| Colour-tuneable light source: | Nein | Envelope:                       | -    |  |  |  |
| High luminance light source:  | Nein |                                 |      |  |  |  |
| Anti-glare shield:            | Nein | Dimmable:                       | No   |  |  |  |
| Product parameters            |      |                                 |      |  |  |  |

|  |  |         | lieters   |              |  |  |
|--|--|---------|---|--------------|--|--|
| Parameter                              |  | Value   | Parameter   | Value        |  |  |
| General product parameters:            |  |         |   |              |  |  |
| 0,                                     | nption in on-<br>00 h), rounded<br>st integer                              | 3       | Energy efficiency<br>class  | E            |  |  |
| indicating if it ro<br>in a sphere (30 | us flux (фuse),<br>efers to the flux<br>50º), in a wide<br>n a narrow cone | 83 in - | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | _            |  |  |
| On-mode p<br>expressed in W            | oower (P <sub>on</sub> ),  | 2,4     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,30         |  |  |
|  | dby power (P <sub>net</sub> )<br>sed in W and<br>second decimal            | -       | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  |              |  |  |
| Outer                                  | Height   | -       | Spectral power  | See image    |  |  |
| dimensions                             | Width  | -       | distribution in the   | in last page |  |  |
| without                                | Depth  | -       | 1   | Soito 1 / 2  |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre)       |      | range 250 nm to 800<br>nm, at full-load  |   |  |  |  |
|--|------|--|---|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | -    | If yes, equivalent power (W)             | - |  |  |  |
|  |      | Chromaticity<br>coordinates (x and y)    |   |  |  |  |
| Parameters for LED and OLED light sources:   |      |  |   |  |  |  |
| R9 colour rendering index value  | -    | Survival factor                          | - |  |  |  |
| the lumen maintenance factor   | -    |  |   |  |  |  |
| Parameters for LED and OLED mains light sources:   |      |  |   |  |  |  |
| displacement factor (cos φ1)   | -    | Colour consistency<br>in McAdam ellipses | - |  |  |  |
| Claims that an LED light<br>source replaces a fluorescent<br>light source without integrated<br>ballast of a particular wattage. | _(b) | If yes then<br>replacement claim<br>(W)  | - |  |  |  |
| Flicker metric (Pst LM)  | -    | Stroboscopic effect<br>metric (SVM)      | - |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;